

Compact Fluorescent Energy Saver Globes

Ideal for use in vanity strips and hanging pendants

ENERGY SAVER

Energy saver globes

Philips Compact Fluorescent Energy Saving Globes provide energy savings and reduce operating costs without sacrificing quality of light compared to incandescent equivalents.

Direct replacement for incandescent bulbs

- Provides warm and inviting soft white light
- Fits into incandescent fixtures
- Similar look of a standard incandescent globe
- Perfect for bathroom vanity strips

Long life

• Lasts 7 years*

Energy savings

 Saves up to \$41 over the life of the lamp when you replace a 75W G40 incandescent globe with a 23W energy saver G40 globe**

* Based on an average daily usage of 3–4 hours per day, 7 days per week.

** Energy savings based on wattage saved x replacement lamp rated average life (8000 hours) ÷ 1000 x \$0.10 kWh rate.



Ordering, Electrical and Technical Data

	Product Number	Description	Volts	Nom. Watts	Approx. Incand. Equiv.	Base	Color Temp. (Kelvin)	CRI	Approx. Initial Lumens ¹	MOL (ln.)	Diam. (In.)	Rated Avg. Life (Hrs.) ²	Min. Starting Temp.	Max. Ambient Temp.
•	15717-2	Vanity Globe EL/A 9 G18	120	9	40G25	Med.	2700	82	400	3 ¾	2.1	8000	-4°F/-20°C	122°F/50°C
•	15718-0	Vanity Globe EL/A 9 G25	120	9	40G25	Med.	2700	82	500	4 ¾	3.1	8000	-4°F/-20°C	122°F/50°C
•	21106-0	Decor Globe EL/A 16 G30	120	16	60G30	Med.	2700	82	900	5 ½	3.75	8000	-4°F/-20°C	122°F/50°C
•	21107-8	Decor Globe EL/A 23 G40	120	23	75G40	Med.	2700	82	1400	6	5.0	8000	-4°F/-20°C	122°F/50°C

Shipping Data

Product Number	SKU UPC (0-46677)	Outer Bar Code (5-00-46677)	Case Qty.	Case Weight (lbs.)	Case Cube (cu. ft.)	Pallet Qty.	SKUs Per Layer	Layers High			Pallet Dimensions (W x D x H)(In.)
15717-2	15717-3	15717-8	6	1.5	0.119	2106	234	9	2.6 x 2.6 x 3.8	5.6 x 8.2 x 4.5	39.4 x 46.8 x 40.5
15718-0	15718-0	15718-5	6	6.0	0.223	1050	150	7	3.3 x 3.3 x 4.9	6.6 x 10.3 x 5.7	37.5 x 45.9 x 38.8
21106-0	21106-6	21106-1	6	3.0	0.39	840	120	6	3.8 x 3.8 x 6.2	12.1 x 8.0 x 7.0	48.5 x 40.0 x 49.0
21107-8	21107-3	21107-8	6	2.1	0.39	420	60	6	5.1 x 5.1 x 5.7	15.8 x 10.7 x 6.0	47.0 x 37.3 x 42.0

1) Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions.

2) Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

Amalgam Technology provides stable light output from -4°F to 122°F.

ENERGY STAR[®] Bulb: As an ENERGY STAR[®] Partner, Philips has determined that this product meets the ENERGY STAR[®] guidelines for energy efficiency. Above specifications subject to change without notice.

WARNINGS & CAUTIONS: Do not use with dimmers. Some electronic timer and photosensor switches contain dimming circuitry, so before using such a switch, check with its manufacturer to ensure compatibility with electronic CFL bulbs. Do not use with emergency exit fixtures or lights. Outdoor use requires a weather-protected fixture. Turn off power before changing bulb. This device complies with Part 18 of the FCC Rules.

Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

Reliable operating temperature range -4F/-20C to 122F/50C.

Note: This product may cause interference with radios, televisions, telephones, or remote controls. If interference occurs, move this product away from device or plug into another outlet.

	-	Ô	Q ,		-					
Bulb Type	Table/Floor Lamp	Outdoor Postlight	Wall Sconce	Surface Mount	Reading Lamp	Border Lights	Recessed Fixture	Open Hanging	Vanity Strip	Ceiling Fan
Decorative Twister	•		•		•			•		
Universal	•	•	•	٠	•	•	•	•		
3-Way	•									
Reflector Flood							•	•		
Dimmable Reflector Flood							•	•		
Candle		•	•		•					٠
Vanity & Decor Globe								•	•	•
Soft White Plus	•	•	•		•	•		•		٠
Outdoor		•				•				
Bug-A-Way		•								
Circline	•									
Genie	٠	٠	٠	٠	•	٠	٠	•	٠	٠



© 2008 Philips Lighting Company. All rights reserved. Printed in USA 1/08

P-8515-B www.philips.com Philips Lighting Company 200 Franklin Square Drive P.O. Box 6800 Somerset, NJ 08875-6800 I-800-555-0050 A Division of Philips Electronics North America Corporation Philips Lighting 281 Hillmount Road Markham, Ontario Canada L6C 2S3 I-800-555-0050 A Division of Philips Electronics Ltd.